



ROUBAIX ACR 1.0

Sizes	(XXS)46, (XS)49, (S)52, (M)54, (M/L)56, (L)58, (XL)61, (XXL)64
Color(s)	Gloss Black/White
Main frame	NEW Fuji Altair 2 custom butted aluminum Integrated 1 1/4" lower head tube, BB-30 bb shell, Ovalize seat tube, Double water bottle mounts
Rear triangle	Fuji C-4 carbon seat stays, Altair 2 aluminum ETC chain stays, Forged road dropout with replaceable derailleur hanger
Fork	NEW FC-770 Fuji Bonded Carbon Integrated w/ 1 1/8" Alloy Steerer
Crankset	FSA Gossamer Pro BB-30 w/ Integrated spindle, 38/52T 7075 CNC AL
Bottom bracket	FSA BB-30 Bearing System
Pedals	Nil
Front derailleur	SRAM Rival, Braze-on
Rear derailleur	SRAM Force
Shifters	SRAM Rival Carbon DoubleTap shifter/brake, 20-Speed
Cassette	SRAM PG-1070, 11-26T 10-speed
Chain	KMC DX-10, 10-sp
Wheelset	Mavic Aksium, 700c clincher
Tires	Continental UltraSport, 700 x 23c Foldable
Tubes	CST presta
Brake set	SRAM Rival dual pivot w/cartridge pads
Brake levers	SRAM Rival DoubleTap
Headset	Tange 1 1/8"U-1 1/4"L Integrated Road, with convex hollow top cap
Handlebar	Fuji CGC Double Butted 6061, 31.8mm w/Anatomical drops
Stem	Fuji CGC Alloy 3D forged, +/-7 degree
Tape/grip	Fuji custom cork wrap
Saddle	Fuji PGC UltraLite Racing
Seat post	Fuji CGC Butted Oversize Alloy, 250mm
Seat clamp	Fuji Superlite Alloy, 34.9mm Laser Etched
Other	7075 alloy water bottle bolts
Weight, kg./lb.	8.58kg / 19.91lbs

- New aluminum race bike with reinforced seat tube, BB30 bottom bracket, oversized chain stays and head tube
- SRAM Force/Rival components
- Also available as a frameset



FC-770 PGC

CompGradeComponents

SIZE	XXS	XS	S	M	M/L	L	XL	XXL
SEAT TUBE, C TO T	460.0	490.0	520.0	540.0	560.0	580.0	610.0	640.0
EFFECT. TT LENGTH	510.0	515.0	530.0	550.0	560.0	570.0	590.0	610.0
CHAIN STAY	410.0	410.0	410.0	410.0	410.0	410.0	410.0	410.0
HEAD TUBE ANGLE	72.0	72.0	72.0	73.5	73.5	73.5	74.0	74.0
SEAT TUBE ANGLE	76.0	75.0	74.0	73.0	73.0	73.0	72.5	72.5
WHEEL BASE	976.0	976.8	982.3	975.9	985.9	995.5	1000.0	1019.0
STAND OVER HEIGHT	732.8	746.1	759.1	777.2	793.9	813.1	840.3	871.5
HEAD TUBE LENGTH	115.0	115.0	115.0	129.0	144.0	164.0	189.0	224.0
REACH	379.0	375.8	381.7	387.5	393.0	397.0	403.8	413.3
STACK	514.0	512.9	512.9	532.8	547.0	566.0	593.4	627.0
STEM LENGTH	90.0	90.0	100.0	100.0	110.0	110.0	120.0	120.0
STEM ANGLE	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
HANDLEBAR WIDTH	400.0	400.0	400.0	400.0	420.0	420.0	440.0	440.0
CRANK LENGTH	165.0	170.0	170.0	172.5	172.5	175.0	175.0	175.0

NOTES: