



SL 1 PRO

SRAM

Sizes	(XS)44, (S)47, (M)50, (M/L)53, (L)55, (XL)58
Color(s)	Carbon/White
Main frame	C-7 Monocoque High Modulus carbon with UD-Marble finish, Integrated aluminum cupped head tube, Double water bottle mounts.
Rear triangle	C-7 High Modulus carbon stays with shaped ride tuned Energy Transfer Chainstay, cold forged dropout with replaceable hanger
Fork	Fuji FC-440 Carbon Monocoque Integrated 1 1/8" Carbon steerer, 420g
Crankset	NEW SRAM Force Hollow Carbon w/ Integrated Spindle, Standard 39/53T
Bottom bracket	SRAM Exterior Bearing system
Pedals	Nil
Front derailleur	NEW SRAM Force Braze-on Type
Rear derailleur	NEW SRAM Force
Shifters	NEW SRAM Force Double Tap shifter/brake, 20-speed
Cassette	SRAM PG-1070, 11-26T 10-speed,
Chain	SRAM PC-1090, 10-speed
Wheelset	Reynold Attack, 700c carbon clincher
Tires	Vittoria Rubino Pro II, 700 X 23c
Tubes	Kenda Ultralite presta tubes
Brake set	NEW SRAM Force dual pivot w/cartridge pads
Brake levers	NEW SRAM Force Double Tap
Headset	Cane Creek IS-21 1 1/8" Integrated Road w/Alloy convex topcap and InterLoc spacers
Handlebar	Fuji PGC Double Butted 7075 Aluminum, 31.8mm Road
Stem	Fuji PGC 7075 Aluminum, +/-5 degree
Tape/grip	Fuji Custom Micro-fibre wrap
Saddle	Prologoo Nago EVO
Seat post	Fuji PGC 7075 Aluminum Oversize 1-Bolt, 300mm
Seat clamp	Fuji Superlite Alloy, 34.9mm Laser Etched
Other	7075 alloy water bottle bolts
Weight, kg./lb.	7.42kg / 16.35lbs

- Each SL-1 model in the series uses the same frame design which varies in carbon materials and components
- Available with new Shimano Ultegra 6700 or New SRAM Force components



SIZE	XS	S	M	M/L	L	XL
SEAT TUBE, C TO T	440.0	470.0	500.0	530.0	550.0	580.0
EFFECTIVE TT LENGTH	510.0	524.9	545.0	555.2	570.0	600.0
CHAIN STAY	405.0	405.0	405.0	405.0	405.0	405.0
HEAD TUBE ANGLE	70.0	71.0	71.5	72.0	72.0	72.0
SEAT TUBE ANGLE	75.0	74.5	73.5	73.5	73.5	73.5
WHEEL BASE	976.5	980.0	987.6	994.0	1000.1	1039.4
STAND OVER HEIGHT	714.2	734.3	758.8	783.0	798.8	817.1
HEAD TUBE LENGTH	110.0	120.0	140.0	160.0	170.0	180.0
REACH	371.0	379.0	384.7	389.0	400.0	428.0
STACK	502.0	515.0	536.5	557.0	570.0	576.0
STEM LENGTH	90.0	100.0	110.0	120.0	120.0	120.0
STEM ANGLE	6.0	6.0	6.0	6.0	6.0	6.0
HANDLEBAR WIDTH	380.0	400.0	400.0	420.0	420.0	440.0
CRANK LENGTH	165.0	170.0	170.0	172.5	172.5	175.0

NOTES: