



SL 1 PRO

SHIMANO

Sizes	(XS)44, (S)47, (S/M)50, (M/L)53, (L)55, (XL)58
Color(s)	Carbon/White
Main frame	C-7 Monocoque High Modulus carbon with UD-Marble finish, Integrated aluminum cupped head tube, Double water bottle mounts.
Rear triangle	C-7 High Modulus carbon stays with shaped ride tuned Energy Transfer Chainstay, cold forged dropout with replaceable hanger
Fork	Fuji FC-440 Carbon Monocoque Integrated 1 1/8" Carbon steerer, 420g
Crankset	NEW Shimano Ultegra Hollow Tech II w/ Integrated Spindle, 34/50T
Bottom bracket	NEW Shimano Ultegra Exterior Bearing system
Pedals	Nil
Front derailleur	NEW Shimano Ultegra Braze-on Type
Rear derailleur	NEW Shimano Ultegra
Shifters	NEW Shimano Ultegra STI Dual Control shifter/brake, 20-speed
Cassette	NEW Shimano Ultegra, 11-25T 10-speed,
Chain	NEW Shimano Ultegra, 10-speed
Wheelset	Mavic Kysrium Elite, 700c Clincher
Tires	Vittoria Rubino Pro II, 700 X 23c
Tubes	Kenda Ultralite presta tubes
Brake set	NEW Shimano Ultegra dual pivot w/cartridge pads
Brake levers	NEW Shimano Ultegra STI
Headset	Cane Creek IS-21 1 1/8" Integrated Road, w/Alloy topcap and InterLoc spacers
Handlebar	Fuji PGC Double Butted 7075 Aluminum, 31.8mm Road
Stem	Fuji PGC 7075 Aluminum, +/-5 degree
Tape/grip	Fuji Custom Micro-fibre wrap
Saddle	Prologoo Nago EVO
Seat post	Fuji PGC 7075 Aluminum Oversize 1-Bolt, 300mm
Seat clamp	Fuji Superlite Alloy, 34.9mm Laser Etched
Other	7075 alloy water bottle bolts
Weight, kg./lb.	7.61kg / 16.77lbs

- Each SL-1 model in the series uses the same frame design which varies in carbon materials and components
- Available with new Shimano Ultegra 6700 or New SRAM Force components



SIZE	XS	S	M	M/L	L	XL
SEAT TUBE, C TO T	440.0	470.0	500.0	530.0	550.0	580.0
EFFECTIVE TT LENGTH	510.0	524.9	545.0	555.2	570.0	600.0
CHAIN STAY	405.0	405.0	405.0	405.0	405.0	405.0
HEAD TUBE ANGLE	70.0	71.0	71.5	72.0	72.0	72.0
SEAT TUBE ANGLE	75.0	74.5	73.5	73.5	73.5	73.5
WHEEL BASE	976.5	980.0	987.6	994.0	1000.1	1039.4
STAND OVER HEIGHT	714.2	734.3	758.8	783.0	798.8	817.1
HEAD TUBE LENGTH	110.0	120.0	140.0	160.0	170.0	180.0
REACH	371.0	379.0	384.7	389.0	400.0	428.0
STACK	502.0	515.0	536.5	557.0	570.0	576.0
STEM LENGTH	90.0	100.0	110.0	120.0	120.0	120.0
HANDLEBAR WIDTH	380.0	400.0	400.0	420.0	420.0	440.0
CRANK LENGTH	165.0	170.0	170.0	172.5	172.5	175.0

NOTES: