



# FINEST 3.0

Sizes	(XS)44, (S)47, (M)50, (L)53
Color(s)	White/Gold
Main frame	Fuji Compact Altair 1 aluminum with Diamond down tube, Double water bottle mounts
Rear triangle	Fuji Altair 1 aluminum, Fuji forged road dropout with replaceable derailleur hanger
Fork	FC-990 Fuji Bonded Carbon Integrated w/ 1 1/8" Cro-mo Steerer
Crankset	Fuji Forged Aluminum 30/42/52T Chainring
Bottom bracket	Sealed Cartridge Bearing ST
Pedals	VP Resin Road w/clips and straps
Front derailleur	NEW Shimano FD-2303, 31.8mm for triple
Rear derailleur	Shimano Sora
Shifters	NEW Shimano ST-2303 shifter/brake, 24-speed
Cassette	SRAM PG-850, 12-26T 8-speed
Chain	KMC Z-72, 8sp
Front hub	Formula Alloy Road, 32H
Rear hub	Formula Alloy Cassette Road, 8-speed, 32H
Rims	Alex RPD-15 Double Wall Aluminum, 32H 700c clincher
Tires	Kenda K-152, 700 X 25c
Tubes	Kenda presta
Brake set	Tektro R-310 Forged AL, dual pivot
Brake levers	NEW Shimano 2300
Brake levers	Tektro RL-570 Top Mount
Headset	V.P. 1 1/8" Standard Semi Cartridge, with convex hollow alloy spacer
Handlebar	Fuji 6061 Butted Road, 26mm Anatomical Drops
Stem	Fuji Adjustable Road, 1 1/8" threadless
Tape/grip	Fuji custom cork wrap
Saddle	Fuji WoS.O. Specific
Seat post	Fuji Comp Micro Adjust alloy, 350mm
Seat clamp	Fuji Superlite Alloy, 31.8mm Laser Etched
Other	7075 alloy water bottle bolts
Weight, kg./lb.	10.87kg / 23.95lbs

- When you're comfortable, you perform better
- Shimano Sora/2300 components



SIZE	XS	S	M	L
SEAT TUBE, CENTER TO TOP	440.0	470.0	500.0	530.0
EFFECTIVE TT LENGTH	505.0	510.0	520.0	535.0
CHAIN STAY	405.0	405.0	405.0	405.0
HEAD TUBE ANGLE	69.0	70.0	69.0	70.0
SEAT TUBE ANGLE	75.0	75.0	74.0	73.5
WHEEL BASE	983.8	983.8	968.0	974.0
STAND OVER HEIGHT	691.0	709.8	742.0	786.0
HEAD TUBE LENGTH	135.0	135.0	150.0	170.0
REACH	360.0	366.0	360.7	362.9
STACK	526.0	526.0	545.5	566.5
STEM LENGTH	90.0	90.0	100.0	110.0
HANDLEBAR WIDTH	380.0	380.0	400.0	400.0
CRANK LENGTH	165.0	165.0	170.0	172.5

**NOTES:**