



TAHOE PRO

Sizes	XS, S, M, L, XL
Color(s)	Gloss Black
Main frame	NEW Fuji Altair 2 custom butted aluminum with Power Curve down tube, Tri shaped top tube, Oversized seat tube and Integrated head tube, double water bottle mounts
Rear triangle	Fuji Altair 2 custom butted aluminum with Edge S-bend MonoStay, Cold forged dropout with CNC'D disc mount and replaceable hanger
Fork	Rock Shox Recon SL Air w/PopLoc Remote LO & 100mm Travel
Rear Shock	n/a
Crankset	NEW Shimano Deore, 22/32/44T Alloy outer ring
Bottom bracket	Shimano ES-25 Octalink Cartidge Sealed Bearing
Pedals	Wellgo ATB w/steel cage, toe clips and straps
Front derailleur	NEW Shimano Deore, 34.9mm
Rear derailleur	Shimano Deore XT Shadow
Shifters	NEW Shimano Deore Rapid Fire, 27-speed
Cassette	Shimano HG-50, 11-34T 9-speed
Chain	KMC HG-73
Front hub	NEW Shimano Deore Sealed Bearing Disc, CL 32H
Rear hub	NEW Shimano Deore Sealed Bearing Disc, CL 32H
Spokes	14G Stainless Steel
Rims	Alex DP-17 Disc Double Wall w/ Single Eyelet 32H
Tires	Continental Race King 26 X 2.2"
Tubes	CST Lite presta
Brake set	NEW Shimano Deore Hydraulic Disc, 180/160mm rotor
Brake levers	NEW Shimano Deore Hydraulic Forged Alloy
Headset	V.P. A-42E 1 1/8" Press Fit Integrated, 30mm spacers
Handlebar	Fuji CGC Riser 15mm double butted aluminum 31.8mm
Stem	Fuji CGC Ultralite Forged Alloy +/- 7 degree
Tape/grip	Fuji Dual Density Kraton rubber
Saddle	WTB Rocket V Comp custom
Seat post	Fuji CGC Forged Al micro adjust, 350mm
Seat clamp	Fuji Superlite Alloy QR, 34.9mm Laser Etched
Weight, kg./lb.	13.05kg / 28.77lbs

- Rock Shox Recon SL Air suspension fork (100mm travel)
- Shimano Deore components



SIZE	XS	S	M	L	XL
SEAT TUBE, CENTER TO TOP	381	432	483	533.4	584.2
EFFECTIVE TOP TUBE LENGTH	543.9	580	605	630	650
CHAIN STAY	420	420	420	420	420
HEAD TUBE ANGLE	70	70	70	70	70
SEAT TUBE ANGLE	73	73	73	73	72.5
WHEEL BASE	1023.5	1058.7	1084.1	1109.7	1124.8
STAND OVER HEIGHT	709.3	733.6	760.5	795.9	825.3
BB HEIGHT	296	296	296	296	296
HEAD TUBE LENGTH	110	115	125	140	155
STEM LENGTH	90	100	110	110	120
HANDLEBAR WIDTH	640	640	640	660	660
CRANK LENGTH	170	175	175	175	175

NOTES: